

BROADCAST INTERMODULATION CONTROL DEVICES

IM PANELS

Model Number	Frequency	Isolator Stage	Pwr: Input Refl	Bandwidth: Fixed	Insertion Loss	Isolation	Load Termination	Actual Dimensions Inches Metric	Ship Wt. lbs kg.
WFM73412	88-108	Single	30 W 15 W		0.55 dB	30+ dB	15 W	3 1/2 x 19 x 4 3/4 89 x 483 x 121	3 1.4
WFM73413	88-108	Single	50 W 30 W		0.55 dB	30+ dB	30 W	3 1/2 x 19 x 4 3/4 89 x 483 x 121	3 1.4
WFM73414	88-108	Single	50 W 50 W		0.55 dB	30+ dB	60 W	3 1/2 x 19 x 7 89 x 483 x 178	5 2.3
WFM73514	88-108	Single	100 W 60 W		0.55 dB	30+ dB	60 W	5 1/4 x 19 x 7 134 x 483 x 178	5 2.3
WFM73515	88-108	Single	100 W 100 W		0.55 dB	30+ dB	125 W	5 1/4 x 19 x 6 1/2 134 x 483 x 166	10 4.6
WFM73514A	88-108	Single	150 W 75 W		0.55 dB	30+ dB	75 W	8 3/4 x 19 x 9 1/2 223 x 483 x 242	10 4.6
WFM73515A	88-108	Single	150 W 150 W		0.55 dB	30+ dB	150 W	8 3/4 x 19 x 9 1/4 223 x 483 x 235	12 5.5
WFM83422	88-108	Dual	30 W 15 W		0.90 dB	60+ dB	15/15 W	3 1/2 x 19 x 5 89 x 483 x 127	6 2.8
WFM83423	88-108	Dual	50 W 30 W		0.90 dB	60+ dB	15/30 W	3 1/2 x 19 x 5 89 x 483 x 127	6 2.8
WFM83424	88-108	Dual	50 W 50 W		0.90 dB	60+ dB	30/60 W	3 1/2 x 19 x 6 1/2 89 x 483 x 166	6 2.8
WFM83524	88-108	Dual	100 W 60 W		0.90 dB	60+ dB	30/60 W	5 1/4 x 19 x 6 1/2 134 x 483 x 166	6 2.8
WFM83525	88-108	Dual	100 W 100 W		0.90 dB	60+ dB	60/125 W	8 3/4 x 19 x 6 1/2 223 x 483 x 166	14 6.4
WFM83524A	88-108	Dual	150 W 75 W		0.90 dB	60+ dB	30/75 W	8 3/4 x 19 x 10 1/4 223 x 483 x 261	14 6.4
WFM83525A	88-108	Dual	150 W 150 W		0.90 dB	60+ dB	60/150 W	8 3/4 x 19 x 10 1/4 223 x 483 x 261	14 6.4
W75311	450-456	Single	20 W 10 W		0.45 dB	30+ dB	10 W	3 1/2 x 19 x 3 3/8 89 x 483 x 86	5 2.3
W75412	450-456	Single	30 W 15 W		0.45 dB	30+ dB	15 W	3 1/2 x 19 x 4 3/4 89 x 483 x 121	5 2.3
W85422	450-456	Dual	30 W 15 W		0.60 dB	60+ dB	15/15 W	3 1/2 x 19 x 5 89 x 483 x 127	5 2.3
W76412	944-960	Single	30 W 15 W		0.45 dB	30+ dB	15 W	3 1/2 x 19 x 5 89 x 483 x 127	5 2.3
W86422	944-960	Dual	30 W 15 W		0.60 dB	60+ dB	15/15 W	3 1/2 x 19 x 5 89 x 483 x 127	5 2.3