

Bandpass Cavity Resonator

Electrical Specifications

Frequency Band	190-240 MHz
Attenuation	See response curve
Input Power (Max.)	200 W
Insertion Loss Range	0.5 - 2.0 dB
VSWR (Max. / Typ.)	1.5:1 / 1.25:1
Electrical Length	1/4 λ
Impedance (Nom.)	50 Ω
RF Connectors	N Female

Mechanical Specifications


Finish	Gray Paint
Number of Cavities	1
Cavity Body Dimensions (WxD)	7" x 7" (178 x 178 mm)
Cavity Height w/ Tuning Rod	26-32.5" (660-826 mm)
Rack Mount	19" EIA (with optional bars or panel)
Overall Size (HxWxD)	26 - 32.5" x 7" x 7" (660-826 x 178 x 178 mm)
Net Weight	8.75 lbs (4 kg)
Ship Weight	16 lbs (7.3 kg)

Environmental Specifications

Operating Temp. Range	-22 to 140 °F (-30 to +60 °C)
-----------------------	-------------------------------



EMR Band Pass Cavities are 1/4 wavelength, high Q cavity filters with excellent selectivity. Bandpass cavities reject frequencies outside of a narrow pass band. These cavities may be factory tuned to specific frequency and are field tunable. Multiple cavities may be connected for greater selectivity with minimal insertion loss and wider pass bandwidths. Multi-cavity configurations come standard with 19 inch EIA rack mounting bars or panel with chassis tray.



Product Notes

- Power ratings listed are based on 1 dB insertion loss setting per cavity.
- Tuning rod maximum height is dependent on frequency.