

INTERMODULATION CONTROL DEVICES

66 - 88 MHz

ISOLATORS & CIRCULATORS

Model No. List Price	Description	Frequency	Pwr: Input Ref1	Bandwidth: Fixed	Insertion Loss	Isolation	Load Termination	Actual Dimensions Inches Metric	Ship Wt. lbs kg.
W7340/2	Single Isolator, 15 Watt Load	66-88	25 W 15 W		0.50 dB	30+ dB	15 W	1 5/8 x 4 1/2 x 5 42 x 115 x 127	4 1.9
W7340/3	Single Isolator, 30 Watt Load	66-88	50 W 30 W		0.50 dB	30+ dB	30 W	1 5/8 x 4 1/2 x 5 42 x 115 x 127	4 1.9
W7340/4	Single Isolator, 60 Watt Load	66-88	50 W 50 W		0.50 dB	30+ dB	60 W	1 5/8 x 4 1/2 x 6 1/2 42 x 115 x 166	4 1.9
W8340/22	Dual Isolator, 15/15 Watt Load	66-88	25 W 15 W		0.75 dB	60+ dB	15/15 W	1 5/8 x 7 1/2 x 5 42 x 191 x 127	5 2.3
W8340/23	Dual Isolator, 15/30 Watt Load	66-88	50 W 30 W		0.75 dB	60+ dB	15/30 W	1 5/8 x 7 1/2 x 5 42 x 191 x 127	5 2.3
W8340/34	Dual Isolator, 30/60 Watt Load	66-88	50 W 50 W		0.75 dB	60+ dB	30/60 W	1 5/8 x 7 1/2 x 6 1/2 42 x 191 x 166	5 2.3



W7340/2



W7340/3



W7340/4



W8340/22



W8340/23



W8340/34