

BROADCAST INTERMODULATION CONTROL DEVICES

ISOLATORS & CIRCULATORS

Model Number	Description	Frequency	Pwr: Input Refl	Bandwidth: Fixed	Insertion Loss	Isolation	Load Termination	Actual Dimensions Inches Metric	Ship Wt. lbs kg.
WFM7340/0	Circulator, 50 Watts	88-108	50 W -		0.40 dB	30+ dB	0	1.1 x 3.45 x 3.42 28 x 88 x 87	4 1.9
WFM7340/2	Single Isolator, 15 Watt Load	88-108	30 W 15 W		0.40 dB	30+ dB	15 W	1.1 x 3.45 x 4.42 28 x 88 x 112	4 1.9
WFM7340/3	Single Isolator, 30 Watt Load	88-108	50 W 30 W		0.40 dB	30+ dB	30 W	1.1 x 3.45 x 4.42 28 x 88 x 112	4 1.9
WFM7340/4	Single Isolator, 60 Watt Load	88-108	50 W 50 W		0.40 dB	30+ dB	60 W	1.1 x 3.45 x 5.92 28 x 88 x	4 1.9
WFM7350/0	Circulator, 100 Watts	88-108	100 W -		0.40 dB	30+ dB	0	3 1/8 x 4 1/2 x 3 7/8 80 x 115 x 99	4 1.9
WFM7350/4	Single Isolator, 60 Watt Load	88-108	100 W 60 W		0.40 dB	30+ dB	60 W	3 1/8 x 4 1/2 x 6 1/2 80 x 115 x 166	4 1.9
WFM7350/4A	Single Isolator, 75 Watt Load	88-108	100 W 75 W		0.40 dB	30+ dB	75 W	3 1/8 x 4 1/2 x 7 5/8 80 x 115 x 194	5 2.3
WFM7350/5	Single Isolator, 125 Watt Load	88-108	100 W 100 W		0.40 dB	30+ dB	125 W	6 1/2 x 8 1/2 x 6 3/4 166 x 216 x 172	7 3.2
WFM7350/0H	Circulator, 150 Watts	88-108	150 W -		0.40 dB	30+ dB	0	5 1/2 x 9 3/4 x 5 1/2 140 x 248 x 140	6 2.8



WFM7340/2



WFM7340/3



WFM7340/4



WFM7350/4